

PRO[®] DUCT 120

Industrial Grade Duct Tape



Technical Data Sheet

Pro[®] Duct 120 is an industrial grade duct tape used for a wide variety of applications.

Features & Benefits:

Waterproof Backing
Highly Conformable
Easy Unwind
Aggressive Adhesive
Indoor/Outdoor use
Excellent high tack
Competitively priced



Technical Data

- ⇒ Adhesive: Natural Rubber
- ⇒ Backing: Polyethylene coated cloth
- ⇒ Thickness: 10.0 mils
- ⇒ Tensile strength: 27 lbs. per inch
- ⇒ Elongation: 17%
- ⇒ Adhesion to steel: 55 oz./in
- ⇒ Colors: Silver, Black, Tan, Brown, Red, Olive Drab, White, Blue, Green, Floral Green, Orange, Yellow, Burgundy, Purple
- ⇒ Service Temperature Range: 50°F to 200°F
- ⇒ Specification: Tested in accordance with UL 723

Application:

Pro[®] Duct 120 is used for carton sealing, book binding, splicing, masking, seat repair, securing or holding and general purpose bundling. Pro[®] Duct 120 can be used as a moisture barrier. Pro[®] Duct 120 typical applications include HVAC, industrial, commercial, utilities, trucking and automotive.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.