

V-REFLEX™ Reflective Material – Silver Segmented Home Wash Reflective Heat Transfer Film #TF-HW506030-25R



Basic Features:

Material	PES
Technology	Micro Glass Bead
Slanted Type	Slant Right
Color	Daytime: Silver. Reflective: High Intensity White.
Width	5cm

Home Wash Guidelines:

Max. Wash Temperature	60°C (140°F)
Bleach	Non-chlorine bleach when needed
Tumble Dry	Low
Dry-clean	30 Cycles
Pressing (Max.)	110°C (230°F)

Care has been taken in construction to maintain quality and performance.

V-REFLEX™ Reflective Material – Silver Segmented Home Wash Reflective Heat Transfer Film #TF-HW506030-25R

Minimum RA (measured at +5.00 entrance and 0.20 observation angles)	500
Intensity of Reflection Compliance	EN ISO 20471, ANSI/ISEA 107
Washing Compliance	ISO 6330

V-Can Reflective Material Co., Ltd

Manufacturing Base
Yongqiao Development Zone,
Sanhuan-Cun, Cao-Cun County, Yongqiao District,
234103, Suzhou, Anhui, CHINA



Nanning V-Can Business Co., Ltd

R&D and Technical Support
International Business Operating Centre
5F-506, No.58, Keyuan Avenue, Hi-Tech District,
530007, Nanning, Guangxi, CHINA

V-Lumix.com

T: +86 771 3186281
T: +86 771 3186171
F: +86 771 3186261

V-Can.com

admin@v-can.com
v-can@v-can.com
biz@v-can.com

V-Can Manufacture Co., Ltd

Manufacturing Base
Part B, Binhai Industrial Park
Economic Development District,
318014, Taizhou, Zhejiang, CHINA

Heat Lamination:

Adhesive Side Liner	None
Reflective Side Liner	PET Film
Lamination Temperature	130-150°C (266-302°F)
Dwell Time (Seconds)	10-20
Line Pressure	Firm (30-40 psi)

Special Instructions: Use of temperatures lower than 40°C will increase the lifetime of the reflective transfer film. Actual lifetime will be dependent upon the detergent system and its dosage level.

Ironing Conditions:

- ✧ Use medium setting, use press cloth.
- ✧ Do not apply steam

Application:

Application on high-visibility warning or fashionable products, such as occupational work wear, consumer garments, sportswear, T-shirt, jacket, stage outfit, shoes and so on.

Storage:

- ✧ Store in a cool, dry area and use within 1 year of receipt.
- ✧ Rolls should be stored in their original cartons, whilst partially used rolls should be returned to their carton or suspended horizontally from the core via a rod or pipe.
- ✧ Cut sheets should be stored flat.

V-Can Reflective Material Co., Ltd

Manufacturing Base
Yongqiao Development Zone,
Sanhuan-Cun, Cao-Cun County, Yongqiao District,
234103, Suzhou, Anhui, CHINA

Nanning V-Can Business Co., Ltd

R&D and Technical Support
International Business Operating Centre
5F-506, No.58, Keyuan Avenue, Hi-Tech District,
530007, Nanning, Guangxi, CHINA



V-Lumix.com

T: +86 771 3186281
T: +86 771 3186171
F: +86 771 3186261

V-Can.com

admin@v-can.com
v-can@v-can.com
biz@v-can.com

V-Can Manufacture Co., Ltd

Manufacturing Base
Part B, Binhai Industrial Park
Economic Development District,
318014, Taizhou, Zhejiang, CHINA